外径	m重量 上段 7.93		ピーリング・酸洗・荒削 丸棒(JIS G 4303)							直·引抜 丸棒(JIS G 4318) (h9)				センタレス 丸棒(h7)			
(mm)	下段 7.98	304	303	メレ作年 316	316L	403	420J2	440C	304	303	316		304	303	316	440C	
0.0	0.005	304	303	310	310L	403	42002	4400		303	310	316L	304	303	310	4400	
0.9	0.006								0								
1	0.009								0								
1.2	0.012								0								
1.4	0.014								0								
1.5	0.016								0								
1.6	0.020								0								
1.8	0.025								0	_	_	_	_	_		_	
2	0.025 0.032								0	0	0	0	0	0		0	
2.3	0.039								0								
2.5	0.042								0				0	0			
2.6									0								
3	0.056 0.056 0.064								0	0	0	0	0	0	0	0	
3.2	0.064								0								
3.5									0	0	0	0	0	0			
4	0.100 0.100								0	0	0	0	0	0	0	0	
4.5	0.126								0								
5	0.156 0.157								0	0	0	0	0	0	0	0	
5.5	0.188	0							0			0					
6	0.224 0.226	0		0	0				0	0	0	0	0	0	0	0	
6.35	0.251								0								
6.5	0.263								0								
7	0.305 0.307	0							0	0	0	0	0	0	0	0	
8	0.399 0.401	0		0	0	0	0	0	0	0	0	0	0	0	0	0	
9	0.505 0.508	0		0	0	0	0		0	0	0	0	0	0	0	0	
9.52	0.565								0								
10	0.623 0.627	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
11	0.754 0.758								0	0	0		0	0	0	0	
12	0.897 0.903	0	0	0	0	0	0		0	0	0	0	0	0	0	0	
12.7	1.00								0			0					
13	1.05 1.06	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
14	1.22 1.23	0	0	0	0	0	0		0	0	0	0	0	0	0	0	
15	1.40 1.41	0							0	0	0	0	0	0	0	0	
15.87	1.57								0								
16	1.61 1.62	00	00	00	00	(H)©	00	00	0	0	0	0	0	0	0	0	
17	1.82 1.83	0	0	0					0	0	0		0	0	0	0	
18	2.03 2.05	00	0	0	0	(H)	0		0	0	0	0	0	0	0	0	
19	2.27 2.28	00	0	0	0	(H)	0	0	0	0	0	0	0	0	0	0	
20	2.51 2.53	00	0	0	0	(H)	0	0	0	0	0	0	0	0	0	0	
21	2.75								0							0	
22	3.04 3.05	00	0	0	0	(H)	0	0	0	0	0	0	0	0	0	0	

440C

	m重量	m重量 ピーリング・酸洗・荒削									直・引抜センタレ				
外径 (mm)	上段 7.93	丸棒(JIS G 4303)						丸棒(JIS G 4318)(h9)				丸棒(h7)			
(111111)	下段 7.98	304	303	316	316L	403	420J2	440C	304	303	316	316L	304	303	316
23	3.29								0	0					
24	3.61 3.63	0	0	0		(H)	0		0	0	0	0	0	0	
25	3.92 3.94	0	0	0	0	(H)	0	0	0	0	0	0	0	0	0
26	4.25 4.28	0	0	0	0	(H)	0	0	0	0	0		0	0	
28	4.93 4.96	0	0	0	0	(H)	0	0	0	0	0	0	0	0	
30	5.65 5.69	0	0	0	0	(H)	0	0	0	0	0	0	0	0	0
32	6.43 6.47	0	0	0	0	(H)	0	0	0	0	0		0	0	
34	7.25 7.30	0	0	0	0	(H)	0	0	0						
35	7.68 7.73	0	0	0	0	(H)	0		0	0	0	0	0	0	0
36	8.13 8.18	0	0	0	0	(H)	0	0	0						
38	9.05 9.11	0	0	0	0	(H)	0	0	0	0	0		0	0	
40	10.0 10.1	0	0	0	0	(H)	0	0	0	0	0	0	0	0	
42	11.1 11.1	0	0	0	0	(H)	0	0	0	0	0		0		
44	12.1	0				(H)									
45	12.7 12.8	0	0	0	0	(H)	0	0	0	0	0	0	0	0	
46	13.3 13.3	0	0	0	0	(H)	0	0							
48	14.4 14.5	0	0	0	0	(H)	0		0						
50	15.6 15.7	0	0	0	0	(H)	0	0	0	0	0	0	0	0	
55	18.9 19.0	0	0	0	0	(H)	0	0	0	0	0				
60	22.5 22.7	0	0	0	0	(H)	0	0	0	0	0				
65	26.4 26.6	0	0	0	0	(H)	0	0	0	0	0				
70	30.6 30.8	0	0	0	0	(H)	0	0	0	0	0				
75	35.2 35.4	0	0	0	0	(H)	0	0	0	0					
80	40.0 40.2	0	0	0	0	(H)	0	0	0	0					
85	45.3 45.5	0	0	0	0	(H)	0	0	0						
90	50.7 51.0	0	0	0	0	(H)	0	0	0						
95	56.5 56.9	0	0	0	0	(H)	0	0	0						
100	62.6 63.0	0	0	0	0	(H)	0	0	0						
105	69.0 69.4	0	0	0					注)定尺品寸法 引 抜 0.9 φ ~ 1.2 φ 1M						
110	75.7 76.2	0	0	0	0	(H)	0	0	1.4				2ϕ 2M.	、4M	
115	82.7 83.2	0	0	0											
120	90.1 90.6	0	0	0	0	(H)	0	0				303センタ 440Cセン		2M、2.1 M 2M	M
125	97.7 98.3	0	0	0						◎印:酸		=			
130	106	0	0	0	0	(H)	0	0	注)	(H) は、(H)品も在			~ 255)	
	107			1	1	I	1	1	注)(H)は、(H)品も在庫有り(硬度HB207~255) 注)重量は参考重量です。 15 φ 以上でピーリングのあるサイズはピーリング						
135	114 115	0	0	0						15 夕以上	でピーリ	ングのある	るサイズは	はピーリング	グ重量で
135	114	0	0	0	0	(H)	0	0		15 φ 以上 引抜、酸	でピーリ 洗の重量		ノグより少	し軽くなり	ます。

です。

(H)

(H)

外径	m重量	ピーリング・酸洗・荒削 丸棒(JIS G 4303)									
(mm)	上段 7.93 下段 7.98	204	202	400 10 4400							
	172	304	303	316	316L	403	420J2	440C			
165	173	0	0	0							
170	182 183	0	0	0	0	0	0	0			
175	193 194	0	0								
180	204 205	0	0	0	0	0	0	0			
185	215 217	0	0	0							
190	227 229	0	0	0	0	0	0	0			
195	239 241	0	0								
200	252 253	0	0	0	0	0	0	0			
210	277 279	0	0	0	0	0	0				
220	304 306	0	0	0	0	0	0				
230	332 334	0	0	0	0	0	0				
240	362 364	0	0	0	0	0	0				
250	392 395	0	0	0	0		0	0			
260	424 427	0	0	0	0	0	0				
270	457 460	0	0	0	0	0	0				
280	492	0	0	0	0	0	0				
290	495 527	0	0	0	0	0	0				
300	531 564	0	0	0	0	0	0				
310	568 602	0	0	0	0						
320	606	0	0	0	0	0	0				
330	646 682	0	0	0	0						
340	724	0	0	0	0						
350	729 767	0	0	0	0	0	0				
360	772 812	0	0	0							
370	817 857	0	0	0	0	0	0				
380	863 904	0	0	0							
390	910 952	0	0	0							
400	958 1002	0	0	0	0	0	0				
420	1008 1104	0	0	0	0						
450	1111 1267	0	0	0	0						
	1275 1441										
480		0	0								
500	1563 1573	0	0	0	0						

■他鋼種

	酸洗	ピーリング	引抜
SUS304L	8φ~ 13φ	16 φ ~ 250 φ	
SUS304N2	9φ~ 16φ	19φ~ 210φ	
SUS309S	8φ~ 16φ	19φ~ 150φ	4φ~ 10φ
SUS310S	6φ~ 16φ	$16\phi \sim 250\phi$	3 φ ~ 18.3 φ
SUS317L	10φ~ 13φ	17φ~ 100φ	
SUS321	13φ~ 16φ	19 φ ~ 150 φ	
SUS329J1	13φ~ 16φ	19 φ ~ 200 φ	
SUS329J4L		$13 \phi \sim 150 \phi$	
SUS630	10φ~ 16φ	$10 \phi \sim 250 \phi$	
SUS403	別表	別表	10φ~ 50φ
SUS430		$16 \phi \sim 200 \phi$	2φ~ 20φ
SUS416	10φ~ 13φ	16 φ ~ 150 φ	
SUS304 丸R品	22 φ ~ 55 φ	16 φ ~ 400 φ	
SUS316 丸R品	22 φ ~ 46 φ	20 φ ~ 400 φ	
SUS304 HL品	8φ~ 25φ		

注)上記サイズにつきましては御問合せください。

- 注) φ165以上は荒削品となります。
- 注)◎印:酸洗品
- 注)(H) は、(H)品も在庫有り(硬度HB207~255) 注)重量は参考重量です。15 の以上でピーリングのあるサイズは ピーリング重量です。
 - 引抜、酸洗の重量はピーリングより少し軽くなります。
- 注) 各材質の色分けは当社識別表示色に対応しています
- 注) 引抜(309S、310L、316L,403、430)、センタレス、HLは切断不 可商品となります
- 注)329J1は13のより切断いたします。403(H)、416は16のより切断致します。引抜(304、303、316)は10のより切断いたします。 酸洗品・ピーリング(304、303、316、316し、317し、304し、304N2、309S、310S、440C、321、403、405、420J2、630)は10々より切断いたします。